DTEN GO with DTEN Mate

DTEN GO

Software	DTEN OS
Display	Utilizes connected display
Placement	Mount above or below TV or display
Camera System	4 Camera array: up to 32ft (10m) coverage Horizontal field of view (HFOV): 160° combined
Audio System	12 Microphone array: up to 32ft (10m) coverage HDMI & 3.5mm Audio Output Acoustic Echo Cancellation Automatic Gain Control (AGC) AI-based Noise Cancellation DTEN Smart Connect
Network	Ethernet (RJ-45) WiFi 2.4Ghz & 5Ghz IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support
Inputs & Outputs	Ethernet LAN (RJ45) x 1 3.5mm Audio Jack x 1 HDMI Out x 2 USB Type-C x 1
In the Box	Power cord and adapter HDMI cable x 2 Ethernet cable x 1
Power	100 to 240 VAC, 50 to 60 Hz
Product Dimensions	10.7 x 2.1 x 2.75 in (272 x 54 x 69mm)
Product Weight	1.3 lb (0.6kg)
Packaging Dimensions	12.7 x 10.7 x 2.25 in (320 x 272 x 57mm)
Packaging Weight	3.55lb (1.61kg)
Operating Temperature and Humidity	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH

DTEN Mate

Software	DTEN Mate OS
Display	LED 10.1" Capacitive Multi-touch Display
Placement	On table or handheld
Network	WiFi 2.4Ghz & 5Ghz
Inputs & Outputs	USB Type-C x 1
In the Box	Power cord and adapter
Power	100 to 240 VAC, 50 to 60 Hz
Product Dimensions	9.38 x 5.8 x 1.0 in (240 x 148 x 25 mm)
Product Weight	1 lb (0.45kg)
Packaging Dimensions	12.6 x 6.8 x 1.5 in (320 x 173 x 38mm)
Package Weight	Approximately <2lb 1kg (Official weight TBD)

v2.2
Copyright DTEN 2021. All Rights Reserved
Details and specifications subject to change without notice. Visit https://dten.com for more information