

Specifications

SMART Chromebox G3

Model SCBOX-CEL-4

Overview

The SMART Chromebox G3 can be connected to a compatible SMART Board® interactive display to provide teachers with a dedicated Chrome $OS^{\text{\tiny{M}}}$ device they can use with their displays.


This benefits teachers who use G Suite as it seamlessly integrates the display with the apps and programs they use every day to teach their students. Teachers will no longer need to have a Chromebook and figure out how to connect it to the display.





Dimensions and weights

Dimensions



Weight

2.8 lb. (1.28 kg)

Shipping dimensions

1.08" × 0.52" × 0.74" 2.75 cm × 1.33 cm × 1.87 cm

Shipping weight

3 lb. (1.4 kg)

NOTE

All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).



As an ENERGY STAR® certified computer, the SMART Chromebox G3 meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

smarttech.com/kb/171643

Hardware

Operating system	Chrome OS			
SMART software	No SMART software is required to be installed on the Chromebox. The software required to enable touch and inking is built in to the SMART Board interactive display's firmware.			
Processor	CPU Intel Celeron 3865U Dual Core 1.8GHz BGA 2MB L3 HD 610			
Memory (RAM)	4G DDR4, 2 slots			
Memory type	2133 DDR4 SODIMM (DDR4-2133)			
Storage	SSD 128G 2242 type			
LAN	Gigabit			
Networking	10 / 100 / 1000M GbE LAN			
WLAN and Bluetooth	802.11ac, BT Combo (2x2) Intel Stone Peak 2 D1 7265 ac 2x2 +Bluetooth 4.2 M.2 non-vPro PCI-e WW with 2 antennas 802.11ac, BT Combo (2x2)			
Wi-Fi capability	Yes			
VESA mounting	100 x 100 mm			
Included cables	1 Power adapter 1 US-type power cord (length 1m)			
Other required cables (not included)	1 USB-A to USB-B 1 HDMI			
Security solution	Kensington lock			

Connectors

Front	1	Audio jack (3.5mm)
	2	USB type-A 3.0 ports
	1	MicroSD™ card reader
Back	1	LAN port
	2	USB 2.0 ports
	1	USB 3.0 port
	1	HDMI port
	1	DC-in jack
	1	USB type-C port

smarttech.com/kb/171643 2

Storage and operating requirements

Voltage	19V	
AC Adapter	65W	
Input	100 to 240V AC, 50 Hz to 60 Hz	
Output	19V DC, 3.42A	
Operating temperature	32°F to 95°F (0°C to 35°C)	
Humidity	30-80%	

Certification and compliance (Model ID: SCB-1)

Regulatory certification

U.S. / Canada	FCC, ISED, UL, CONEG Packaging, California Proposition 65, Conflict Minerals	
EU / EEA / EFTA	CE - CB, RED, REACH, RoHS, WEEE, Battery and Packaging Directives; REACH and POP Regulations	
Australia / New Zealand	RCM	

Compatible SMART Board interactive displays

Display	Models	
SMART Board 7000R and 7000R Pro	• SBID-7075R	• SBID-7075R-P
	• SBID-7086R	• SBID-7086R-P
	• SBID-7275R	• SBID-7275R-P
	• SBID-7286R	• SBID-7286R-P
SMART Board 7000 and 7000 Pro	• SBID-7275-V2	• SBID-7275P-V2
	• SBID-7286-V2	• SBID-7286P-V2
	• SBID-7075	• SBID-7075P
	• SBID-7086	• SBID-7086P
	• SBID-7275	• SBID-7275P
	• SBID-7286	• SBID-7286P
SMART Board MX (V2)	• SBID-MX265-V2	
	 SBID-MX275-V2 	
	• SBID-MX286-V2	
SMART Board 6000S and 6000S Pro	• SBID-6265S	• SBID-6265S-P
	• SBID-6275S	• SBID-6275S-P
	• SBID-6286S	• SBID-6286S-P

smarttech.com/kb/171643

Specifications

SMART Chromebox G3 - Model SCBOX-CEL-4

Purchasing information

Order numbers

1034128 SMART Chromebox G3

Warranty

Warranty 3-year Limited Equipment Warranty. See https://support.smarttech.com/forms/warranty-form

smarttech.com/support smarttech.com/contactsupport

© 2020 SMART Technologies ULC. All rights reserved. SMART Board, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. All third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. May 19, 2020.

smarttech.com/kb/171643 4